





- Duct fan with circular connections.
- Proven performance and reliability.
- Compact with high capacity and efficiency.
- Low sound levels.
- Operational in both 50 and 60 Hz.
- Impeller with backward curved blades.
- The external rotor motor has maintenance-free sealed ball-bearings and is very energy efficient.
- For speed control a transformer or electronic speed controller can be connected.
- Integrated motor protection.
- Junction box has enclosure class IP 54.
- Fan housing is manufactured from galvanized sheet steel.
- The fan is intended to be installed in a duct system.
- A duct connected fan can be installed outside or in damp environments.
- Easy installation in any position.


PRESSURE/FLOW



POWER/FLOW



SFP



TECHNICAL DATA

Voltage	230 V
Frequency	50 Hz (60 Hz)
Phase	1 ~
Current	0.63 A
Power	145 W
Speed	2750 r.p.m.
Max. temp of transported air	80 °C
Sound pressure level, 3 m	45 dB(A)
Weight	4.7 kg
Enclosure class	44 IP
Wiring diagram	4040001

ACCESSORIES

- Mounting bracket Kit MB
- Mounting clamp MK 200
- Safety grille BSV 200
- Back draught shutter RSK 200
- Louvre YG 200
- Louvre shutter VK 200
- Filterbox FLK 200
- Filterbox FLF 200
- Silencer LDC 200
- Transformer controller VRTE C
- Transformer controller VRDE 1.5
- Speed controller VRS 1.0

SOUND DATA

	L _{wa} tot dB (A)	63	125	250	500	1K	2K	4K	8K
Surrounding 230 V	52	27	34	41	46	48	44	44	35
Outlet 230 V	75	58	60	69	69	67	66	64	59
Inlet 230 V	74	55	62	67	69	66	63	62	57
Inlet 165 V	70	51	59	64	64	62	59	58	49
Inlet 135 V	61	45	53	56	56	52	51	45	35
Inlet 110 V	51	37	47	45	45	42	34	25	18
Inlet 80 V	47	39	45	38	36	30	18	12	13

MORE INFORMATION



Find out the latest updated information about this product by visiting www.ostberg.com or scanning this QR code.

DIMENSIONS (mm)

